

SA-YQ60 hydraulic puller

. order number :07031

Essential parameter

Maximum linepull (kN):60

Continuous linepull (kN):50

Maximum linespeed (km/h):5

Bullwheel bottom of groove diameter(mm): Φ 460

Bullwheel grooves number : 7

Maximum suitable steelrope diameter (mm): Φ 18

Maximum through connector diameter (mm): Φ 60

Engine power /speed (kW/rpm):77/2800

Dimensions (mm):3800×2100×2300

Weight (kg): 3000

Feature :

- 1.ininitely variable speed and linepull control ,the pull in the rope can be read on the line pull gauge .
- 2.the max pull for conductor–stringing operation can preset ,automatic overpull protection system .
- 3.spring applied –hydraulic release brake acts automatically in case of hydraulic failure ensure to safety .
- 4.attached reel winder with automatically level wind .load and unload conveniently

Main component :

1. engine : Cummins(DONGFENG) water cooled engine.
2. main variable pump and main motor :rexroth (BOSCH)
3. Reducer :RR (Italian)
4. main hydraulic valve : rexroth (BOSCH)
5. Radiator : AKG
6. hydraulic instrument :WIKA
7. Mating with model GSP1400 drum (order number :07125A)
8. If you choose Cummins (USA) water–cooled diesel motor, the mode is “YA-YQ60A”,order number:07032.

