

### Anti –twisting braided steel rope

| Order number | Structure              | Diameter(mm) | Single bundle diameter (mm) | Breaking force (kN) | Production length (m) |
|--------------|------------------------|--------------|-----------------------------|---------------------|-----------------------|
| 18101        | Square eight strands   | 7            | Φ2.0                        | 34.38               | 1000                  |
| 18102        |                        | 9            | Φ2.5                        | 53.90               |                       |
| 18103        |                        | 11           | Φ3.0                        | 76.94               |                       |
| 18104        |                        | 13           | Φ3.5                        | 105.04              |                       |
| 18105        |                        | 15           | Φ4                          | 116.6               |                       |
| 18109        | Square twelve strands  | 11           | Φ2.5                        | 80.8                | 800                   |
| 18110        |                        | 13           | Φ3.0                        | 115.4               |                       |
| 18111        |                        | 15           | Φ3.5                        | 157.55              |                       |
| 18112        |                        | 18           | Φ4.0                        | 206.27              |                       |
| 18113        |                        | 20           | Φ4.5                        | 260.3               |                       |
| 18118        | Hexagon twelve strands | 11           | Φ2.5                        | 80.8                | 1000                  |
| 18119        |                        | 13           | Φ3.0                        | 115.4               |                       |
| 18120        |                        | 15           | Φ3.5                        | 157.5               |                       |
| 18121        |                        | 18           | Φ4.0                        | 205.71              | 800                   |
| 18122        |                        | 20           | Φ4.5                        | 260.34              |                       |
| 18123        |                        | 24           | Φ5.0                        | 320.82              |                       |
| 18140        | Hexagon eighth strands | 21           | Φ3.0                        | 173.1               | 600                   |
| 18141        |                        | 24           | Φ3.5                        | 236.33              |                       |
| 18151        |                        | 27           | Φ4.0                        | 309.40              |                       |
| 18152        |                        | 30           | Φ4.5                        | 389.28              |                       |
| 18153        |                        | 33           | Φ5.0                        | 481.22              |                       |
| 18154        |                        | 36           | Φ5.5                        | 581.75              |                       |

·Uses :applied to mechanical pulling and tensioning release conductors ,unsuitable to pulling ropes for small diameter winch .

·feature: braided1960 Mpa high-strength galvanized steel wire .rotation resistance during pulling .supple and disperse resistance .

·Notes : the specification and length of steel can custom according to your request .

