

SA-YZ2×50 hydraulic Tensioner

.Order number :07195

· Essential parameter

Maximum Tension(kN): 2×50 or 1×100

Continuous Tension(kN):2×45 or 1×90

Maximum speed (km/h):5

Bullwheel bottom of groove diameter (mm) :Φ1500

Number of grooves:2×5

Maximum pullback (kN):2×50or 1×100

Maximum speedback (km/h):2×1

Maximum suitable conductor diameter (mm): Φ40

Engine power /speed (kW/rpm):51/2500

Dimensions (mm): 5130×2250 ×2910

Weight(kg):6500

·uses :used to string various conducts and earthwire . it as one pull one or one pull four using .

·feature :

1. Bullwheel with wearproof MC nylon lining segments.
2. Infinitely variable tension control and constant tension conductor stringing .
3. Spring applied hydraulic released brake acts automatically in case of hydraulic failure to ensure safety .
4. attached two sets of hydraulic power output interface to connect hydraulic conductor reel stand ..

·Main component :

- 1.Engine :Deutz air-cooled diesel engine.
- 2.main pump and main motor :Rexroth (BOSCH)
3. Main hydraulic valve :Rexroth (BOSCH)
4. Reducer : R.R(Italian)
- 5.Radiator :AKG
- 6.Hydraulic instrument :WIKA
7. it can choose the Chinese Deutz air-cooled engine.