

Quick manual hydraulic press

Order number	16192	16193
Model	YQK150	YQK200
Maximum compression (kN)	150	200
Stroke (mm)	22	30
Range of compression joint	Cupreous terminal and connector :16~185 mm ²	
	Aluminous terminal and connector :16~240 mm ²	
	Clamp pressing tube :LJ25-95,LGJ25-95	Clamp pressing tube :LGJ 35-240
Weight (kg)	5.2	7.7
Module shame	Hexagon :Mould :	Hexagon :Mould :
	16.25.35.50.70.95.120.150.185.240. mm ²	35.50.70.95~120.150.185.240. mm ²
	Arc mould :LJ25.35.50.70.95 LGJ25.35.50.70.95	Arc mould : LGJ35.50.70.95.120. 150.185.240

Notes :Attached a set of hexagonal compression die sets at random .the other compression die sets can be selectively matched .



Model QY12S manual hydraulic press

Order number	Maximum compression (kN)	Applicable Terminal	Oil capacity (ml)	Weight (kg)
16195	120	Cupreous terminal 16~300 mm ² Aluminous terminal 16~240 mm ²	140	6

- uses:use to compress the cupreous –aluminous terminal .
- feature :1.integrated double -speed manual pump ,operated quickly .
- 1. C type jaws ,rotary head ,operate conveniently .
- note :1.carry iron package .

2.mating 10 sets of YML 12 hexangular press die (25~300 mm²)(order number :16195A)

