

SA-YZ2×35 hydraulic Tensioner

·Order number :07181

·Essential parameter

Maximum Tension(kN): 2×35 or 1×70

Continuous Tension(kN):2×30 or 1×60

Maximum speed (km/h):5

Bullwheel bottom of groove diameter(mm) :Φ1200

Number of grooves:2×5

Maximum pullback (kN):2×30 or 1×60

Maximum speedback (km/h):2×1.2

Maximum suitable conductor diameter (mm): Φ32

Engine power /speed (kW/rpm):38/2500

Dimensions (mm): 4100 × 2100×2600

Weight(kg):4000

·uses :used to string various conducts and earthwire .

·feature :

1. Bullwheel with wearproof MC nylon lining segments.
2. Infinitely variable tension control and constant tension conductor stringing .
3. Spring applied hydraulic released brake acts automatically in case of hydraulic failure to ensure safety .
4. attached two sets of hydraulic power input interface to connect the hydraulic conductor reel stand .

·Main component

- 1.Engine :Chinese famous brand water-cooled engine .
- 2.main pump and main motor : Rexroth (BOSCH)
- 3.Reducer : RR(Italian) or Rexroth
- 4.hydraulic valve : Rexroth (BOSCH)
- 5.radiator :AKG
- 6.hydraulic instrument :WIKA
- 7.it can choose :Deutz air-cooled engine.