

Fiberglass duct rodder

Uses : suitable for tube optical cable installation in power communication industry .

·component :fiberglass duct rodder is composed of rodder and small wheel .

There are nylon guide tip and nylon shackle for fiberglass duct rodder with terminal end threaded 12mm . the standard length of roller guide tip is 100m.

·feature :rodder adopt FRP molding core material . the external cover with special engineering plastics. Smooth and high-strength .

Model CSP1 fiberglass duct rodder adopt $\Phi 11$ mm roller guide tip, order number is :21421

Model CSP1 fiberglass duct rodder adopt $\Phi 13$ mm roller guide tip, order number is :21422

Model CSP1 fiberglass duct rodder adopt $\Phi 15$ mm roller guide tip, order number is :21423

Note :please note in contract if need other length .

The following attachment supplied accessories for duct rodder



Order number	Spec	Feature	Use
21425	ZT25Cone-shaped guide tip	Cone-shaped tip $\Phi 25$	Guide rodder through duct ,the tip of model Z25 with hole ,apply to pullback connect pulling rope .
21426	ZT40Cone-shaped guide tip	Cone-shaped tip $\Phi 40$	
21427	DXL60 guide roller	Circumcircle $\Phi 60$	Guide rodder through swerve and level end of duct .
21428	NC mud basket	Close valve $\Phi 60$	To clean mud and other small thing
21429	XZM12N swivel joint	Out diameter $\Phi 25$	Connect the rodder




21429



21428



21425



21427



21426