

Stringing Blocks



Table 1: Dimensions of Stringing Blocks

Item number	Block	Number of wheel	Block length (mm)	Height (mm)	Features
10101	1010101	1	20	33	Rubber lined Aluminium sheave
10102	1010102	2	40	41	Mildle steel sheave side / Rubber lined Aluminium sheave
10103	1010103	2	60	54	
10104	1010104	1	20	33	MC Nylon sheave
10105	1010105	2	40	47	Mildle steel nylon sheave Conductor / Rubber lined Aluminium sheave
10106	1010106	2	60	75	
10107	1010107	1	40	44	
10108	1010108	2	60	75	MC Nylon sheave

- + Note: 1. Suitable for conductors up to ACB400.
 2. Block dimension (outside diameter + out diameter + sheave width) 1000-1050-100mm

Table 2: Dimensions of Stringing Blocks

Item number	Block	Number of wheel	Block length (mm)	Height (mm)	Features
10111	1010201	1	30	50	Rubber lined Aluminium sheave
10112	1010202	2	40	100	Mildle steel sheave conductor / Rubber lined Aluminium sheave
10113	1010203	2	60	100	
10114	1010204	1	30	34	MC Nylon sheave
10115	1010205	2	60	50	Mildle steel nylon sheave Conductor / Rubber lined Aluminium sheave
10116	1010206	2	60	100	
10117	1010207	2	40	75	
10118	1010208	2	60	100	MC Nylon sheave
10119	1010209	1	60	100	Mildle steel sheave conductor / Rubber lined Aluminium sheave
10120	1010210	1	70	100	Mildle steel sheave conductor / MC Nylon sheave

- + Note: 1. Suitable for conductors up to ACB400.
 2. Block dimension (outside diameter + out diameter + sheave width) 1000-1050-100mm
 3. 10112/13 / 10118 mildle steel sheave width 90 (feature can provide the alternative mildle nylon of width 90 (mm).